WEST Search History

Hide Items	Restore	Clear	Close

DATE: Sunday, May 09, 2010

Hide?	Set Name	Query	Hit Count
Interference			
DB=PGPB,USPT,UPAD; PLUR=YES; OP=ADJ			
☐	L14	L13 and (context switch).clm.	1
☐	L13	L12 and emulat $.clm.	93
☐	L12	(verify $ same program $).clm.	9290
Prior Art			
DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ			
☐	L11	L9 and (compar$ same target)	38
☐	L10	L9 and (compar$ same (subject and target))	8
☐	L9	L5 and context switch	162
☐	L8	L7 and context switch	8
☐	L7	L5 and (compar$ same (subject and target))	32
☐	L6	L5 and (subject same target)	70
☐	L5	L4 and ((convers$ or convert$) near2 (program$ or code))	1722
☐	L4	emulat$ and verif$	20961
☐	L3	L2 and context switch	10
☐	L2	L1 and emulat$ and verif$	171
☐	L1	717/134-139.ccls.	2145

END OF SEARCH HISTORY

Google | verify program code conversion emulator "context switch" | Search   Advanced Sea

Web Show options...

Results **1 - 10** of about **11,900** for **verify program code conversion emulator "context switch"**. (**0.17** seconds)

(WO/2004/042564) METHOD AND APPARATUS FOR PERFORMING VALIDATION OF ...
A method of **verifying program code conversion** performed by an **emulator** (30a), ... comprising the step of performing a **context switch** between at least an ...
www.wipo.int/pctdb/en/wo.jsp?KEY=04%2F42564.040722... - Cached

> ### (WO/2004/042564) METHOD AND APPARATUS FOR PERFORMING VALIDATION OF ...
> A **context switch** is performed, by executing a **context switch** routine, ... Then, the first **emulator** 30a is used to **verify program code conversion** as ...
> www.wipo.int/pctdb/en/wo.jsp?KEY=04%2F42564.040722... - Cached
>
> Show more results from www.wipo.int

Method and apparatus for performing incremental validation of ...
by JH Sandham
Nov 4, 2004 ... A method and apparatus for **verifying program code conversion** performed by an **emulator**. A first **emulator** configured in a same-to-same (X-X) ...
www.freepatentsonline.com/y2004/0221273.html

SEGGER Microcontroller - Context switching time
The time needed for a complete **context switch** including the time needed to switch the LED ... Download the sample project below to test, compare and **verify** our context ... The following source **code** is excerpt from MeasureCST_Scope.c: ... The example **program** calculates and subtracts the measurement overhead itself, ...
www.segger.com/cms/**context-switching-time**.html - Cached - Similar

CS 162 Project Phase 3
(30%) Implement lazy loading of the **code** and data pages from user programs. That is, rather than reading all of the **code** and data from a user **program** at ...
inst.eecs.berkeley.edu/~cs162/fa07/Nachos/phase3.html - Cached

Tics Realtime Kernel Definitions
In self-booting embedded systems, the **program code** is stored in FLASH. ... setting a breakpoint in ROM, mapping **emulator** memory to target board .... The hex file however, takes more time to load because ascii to binary **conversion** must be ..... and a **context switch** is performed to the previously suspended task. ...
www.concentric.net/~tics/ticsdef.htm - Cached - Similar

DevelopersGuide/ProgrammingMinix - Minix Wiki
Mar 12, 2010 ... What **programming** languages and compilers are supported by Minix? .... On a **context switch** Minix merely sets the "don't use FP" bit in some register. Costs? ... This isn't much work, we can simply take Minix-vmd's **code**, ...
minix3.org/doc/environ.html - Cached - Similar

[PDF] Project 3: Demand Paging
File Format: PDF/Adobe Acrobat - Quick View
For this project, we provide no new **code**—running inside the proj3 subdirectory will cause

nachos .... for the clock algorithm), and a **context switch** occurs. ...
cseweb.ucsd.edu/classes/su09/cse120/p3.pdf

[PDF] MDK4_ pdf.cdr
File Format: PDF/Adobe Acrobat - Quick View
The Debugger provides **Code** Coverage statistics to **verify** applications that require certification
testing ... **program**. **Code** coverage identifies every instruction that ... Unlimited. **Context Switch**.
<4 S. Memory Requirements. **CODE** Space ...
www.keil.com/product/brochures/mdk_2010.pdf

Thread-Based Virtual Duplex Systems in Embedded Environments
Therefore, we propose virtual duplex systems using **emulated** multithreading. .... The **program code**
is divided into instruction blocks ranging in size from one to .... A is the **context switch** frequency of
a virtual duplex system with ...
doi.ieeecomputersociety.org/10.1109/MM.2005.39

Searches related to **verify program code conversion emulator "context switch"**

kernel context switch   context switch overhead

1 2 3 4 5 6 7 8 9 10   Next

verify program code conversion emulator "context switch"   Search

Search within results - Language Tools - Search Help - Dissatisfied? Help us improve - Try Google Experimental

Google Home - Advertising Programs - Business Solutions - Privacy - About Google